


Sulfuric Acid Storage Tanks That Last


USE THE BEST MATERIAL FOR THE JOB




Unexposed FRP @ 400 ft. pounds @ -40° F.



HDLPE #880046 exposed 6 months in 98% H₂SO₄ 400 ft. lbs. @ -40° F.



XLPE exposed 6 months in 98% H₂SO₄ 3.4 ft. pounds @ -40° F.



XLPE with linear liner (delamination example)

Sulfuric Acid to 98% Concentration

HDLPE resins #880046, natural in color, 1.9 specific gravity, 600 psi, meets ASTM standards and Snyder Industries provides a FULL 3 YEAR WARRANTY for storage at ambient temperatures.

Specify the correct tank material...one that you can depend on...a material that has been proven to be the best overall for the storage of Sulfuric Acid!

The resin that Snyder recommends is a "true" high density linear resin. Unlike other tank manufacturers who try to achieve the same results using a Linear LOW Density liner in a XLPE tank, Snyder uses the **better material, for the whole tank** - providing much higher tensile strength, and chemical resistance.

Additional advantages over lined tanks: you don't have the potential problems of total coverage of the linear material over the XLPE material during processing; and, delamination as a result of the constant filling and emptying processes associated with storage tanks in general. Our HDLPE resins have a higher density and a higher tensile strength than Phillips Marlex XLPE, the most recognized XLPE in the industry.

The **High Density** linear resin that Snyder uses provides:

- the best chemical barrier
- best chemical resistance
- best tank life, and is
- repairable by welding if the tank is ever damaged.

(Snyder recommends the use of PVDF or Corzan CPVC fittings with Viton gaskets and Hastelloy bolts for sulfuric acid storage.)

Don't let the wrong tank material leave you open to chemical attack!



P.O. Box 4583 • Lincoln, NE • 68504 • 402-467-5221 • Fax: 402-465-1220

Other manufacturing locations: Marked Tree, Arkansas • Philippi, West Virginia • Chowchilla, California • 559-665- 7611 • Fax: 559-665-5807

www.snydernet.com